

WASTE RECOVERY AND SPILL CONTAINMENT SYSTEM – VACUUM / RECYCLE CAPABILITY

The **WRSC1** Waste Recovery and Spill Containment System is a full “Closed Loop” Vacuum & Recycle Trailer. The two 270 Gallon water tanks provide 540 Gallons of water and allow an operator to Vacuum Captured Waste Water/Spill back to the **AZV88** (with Scupper tool provided) which provides 7 stages of filtration that separates oil and returns the grey water back to the water tanks with 5 micron purity. Included are:**ASF01** (Start up Filter Kit), **(2) ZMAT7** (6 ft Containment Berms)

The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. The SC35006DAF ALL DIESEL Pressure Washer has 3500 psi @ 5.5 gpm cleaning power with variable pressure, temperature and water flow to meet the challenge of multiple cleaning tasks.

* Items supplied in package.

TECHNICAL SPECIFICATIONS	WRSC1
PRESSURE WASHER	SC35006DAF
FLOW CAPACITY	5.5 GPM
OUTLET TEMPERATURE	Panel Mounted Adjustable Thermostat to 200°F
ENGINE	17 hp KUBOTA Diesel Twin Cylinder Water Cooled
ENGINE/BURNER FUEL CAPACITY	Diesel # 2, 18 Gallon for Burner/ Engine
CONTROL / SWITCHES	Key Start, Lighted Burner On/Off Switch, Water Tight Electrical Box, Hour Meter
BATTERY	EB78S Sealed (Fitted)
PUMP	Triplex Ceramic Plunger Piston V - Belt Drive Low RPM General Pump ,Brass Head & APS50 Seal Saver Kit
PRESSURE CONTROL	Adjustable Pressure Unloader / Regulator , Safety Burst Disc
HOSES/WAND/TRIGGER GUN	AH105 Sub100” HP Hose/ AVWA3 Adjustable Spray Wand /Trigger Gun
SPRAY NOZZLES	#5.5,#5,#4 & # 2.7 (15 Degree)
BURNER / COIL	½” Schedule 80 Steel Coil, 4 Pancake ,Ceramic Insulation, SS Coil Enclosure
BURNER / POWER	2900 Watt Generator /Diesel Fired, 115v, Automatic Ignition, Raycor Fuel Filter
CONSTRUCTION	Powder Coated Pro-Tect-It Frame
MOUNTED/FULLY PLUMBED TO	-----
TANDEM TRAILER	T500EE
SUSPENSION / AXLE	2) 3700# Torsion axles-up to 300% more wheel travel over conventional trailers
TRAILER BRAKES	Electric Brakes on both axles, Breakaway Switch
WHEEL / TIRE	4)14” White Spoke Rims,5 Lug,ST205/75D/14Tires,1760# capacity P/tire @ 35psi
VEHICLE HITCH / GVWR	TC136 3” Adjustable Lunette Eye / 7000# GVWR
FENDERS	12 GA Steel Fender with recessed Tail Light mount
LIGHTS	Recessed Rubber Grommet Snap-In, 4 Pole Flat Wiring Connector, DOT Approved
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8” Diameter
WATER TANK	540 Gal. total capacity (dual 270 gal) seamless polyethylene, 10” lid, garden hose fill fitting
TANK DRAW / FILTER	1½” 80 Mesh Strainer with Drain, 1½” Fast Drain Valve
HOSE REELS	1 x AR200 HP Hose Reel & 1 x AR201 LP Hose Reel & AG100 /100” Inlet Hose
CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish
STORAGE	Accessory Storage Compartment in rear of Trailer under AZV88
WEIGHT / DIM	2500 Lbs. (Total Unit Packaged) 168 ” L x 72 ”W x 72”H

WRSC1- WASTE RECOVERY AND SPILL CONTAINMENT SYSTEM



Global Warranty: Big 6 Years on Heating Coil / 5 Years Pump Crankcase
2 Years Manufacturer Warranty Diesel Engine
1 Year Trailer Frame/Pressure Washer Frame/Panels/Parts

Certification:



ETL Listed
Certified to UL 1776
Certified to
CAN / CSA B140.11



Manuals / Wiring Diagrams /Spare Parts Exploded Views Included (Spare Parts Proposals available on request)

All items are on our GSA Contract Schedule GS07F0369M Expires 05/31/2012
Cage Code: OGUR9 Duns: 153685474 Federal Tax ID : 330236912

FREE Freight Continental USA - F.O.B. Origin Puerto Rico / Alaska / Hawaii
International Delivery Locations Quotations by request
Palletized for Safe Shipping, Some Assembly required, Wheels /Fenders/Tongue etc
Manufacturing Lead Time to Shipping 14-15 Days A.R.O.

For further information please contact David Sholson GSA Sales Manager/Administrator
Hydro Tek Systems, Inc 2353 Almond Ave Redlands, CA. 92374
Telephone Direct: 1-909-583-9911 Fax Direct: 1-909-799-9888 Email: dsholson@hydrotek.us Web: www.hydrotek.us